



SSA INC. NATIONAL TITLES

SUPER SEDAN TITLE

2009 - Lismore Speedway, Lismore Showgrounds, NSW on 18th, 19th & 20th & 21st February
2010 – Speedway City, Virginia, SA on 3rd, 4th, 5th and 6th March

MODIFIED PRODUCTION TITLE

2009 - Attwell Park Speedway, Albany, WA on 10th, 11th & 12th April
2010 – Latrobe Speedway, Latrobe, TAS on 11th, 12th and 13th March

STREET STOCK TITLE

2009 - Carrick Speedway, TAS on 8th, 9th & 10th January
2010 – Ellenbrook Speedway, WA on 23rd, 24th and 25th April

PRODUCTION TITLE

2009 – Wangaratta Motorsports Club, VIC on 5th, 6th and 7th February

JUNIOR TITLE

2009 - Timmis Speedway, Mildura, VIC on 15th, 16th and 17th January
2010 – Latrobe Speedway, Latrobe, TAS on 14th, 15th and 16th January

Information and nomination forms for the above events will be posted on our website under the divisions heading and relevant class approximately 2 months prior to the event. www.speedwaysedans.com

SUPER SEDAN SPECIFICATION MANUAL DRAFT

States will be holding a meeting with their drivers (if they haven't already done so) to vote on the following item:

Panhard bars adjustable from the driving compartment are not allowed.

CLARIFICATIONS FOR ALL SECTIONS

Towing attachments will be via the override bars or a hole cut in the panel under the bumper, to allow the bumper pipe to be used to pick up the vehicle.

If a car has faults entered in the logbook and they have not been fixed by the next race meeting the car will not race. The log book must be confiscated and posted back to their Club Secretary. The driver will get the book back once cleared by their Machine Examiner.

CLARIFICATIONS FOR JUNIOR SEDANS

1. Adjustable or variable cam timing gears are not permitted and can only be standard O.E.M. equipment gears. Manufactured, modified, sports or racing parts are not permitted.
2. Page 32 Section 23b Add: Tailshaft loop may also be 6 mm wire rope as per other section specification books.
3. 200 mm is the maximum distance forward or back from the "A" leg of rollcage for the fitment of a subframe crossbrace bar before gussets are required.
4. Underslung fuel tank is a fuel tank that has some portion below the bumper or chassis rails and therefore is to have fuel tank protector bar fitted.

NEW POLICY ITEM

That no junior competitor, whilst competing in a junior event, will receive prize money,

CLARIFICATIONS FOR PRODUCTION SEDANS

1. Plastic bumper cover must be fitted with round head bolts. Aluminium rubbing strips optional. 40 mm x 3 mm aluminium strip maximum. May be fitted between bolts to support bumper cover.
2. Clarification of Commodore VT onwards: Stub axles bearing carrier assembly is classed as the stub axle assembly.



CONT... CLARIFICATIONS FOR PRODUCTION SEDANS

3. Underslung fuel tank is a fuel tank that has some portion below the bumper tube or chassis rails and therefore is to have a fuel tank protector bar fitted.
4. Any front mud protector guards under cars to protect engine or suspension components from mud and dirt must not be lower than 150 mm from the ground and must not attach to bumper cover.
5. Track measurements VT, VX & VY Commodore and Monaro: Front 1620 mm, Rear 1640 mm
6. 200 mm is the maximum distance forward or back from the leg of roll cage attached to bottom bar for the fitment of a subframe crossbrace bar before gussets are required.
7. Wheelbase measurements for XD/XE Falcon should be 2818mm.

CLARIFICATIONS FOR MODIFIED PRODUCTION SEDANS

1. Plastic bumpers must be fitted with round head bolts. Aluminium rubbing strips optional. 40 mm x 3 mm maximum aluminium strip may be fitted between bolts to support bumper cover.
2. Holden Commodore VT-VZ, be permitted to replace the front strut assembly, with a coil over shock absorber, spring and top "A" Arm. The lower end of the coil over must mount directly to the bottom suspension arm and to the inner guard skirt at the top, in a similar position to the EA onwards Falcon. A manufactured top arm must mount directly to the OEM spindle, via a manufactured ball joint mounting. This arm is to mount to the OEM Inner guard skirt at a point 165mm from the lower edge of the front subframe.

** Reason: as directed by the board to maintain class parity, due to the deletion of the 50mm of strut ruling, a Falcon can mount a coil over unit directly into the car. This is not possible with any car using a Mcpherson strut type suspension. Using the dimensions supplied, the roll centre will be identical to a Falcon using the 50mm extension the stub axle. Technical committee approval to be sought for other individual vehicle types as they are brought forward.

3. Page 34 Section Suspension 22C: Original front sub axles must be used (to include) bearing carriers on later Commodore (classed as stub axle assembly)
4. Underslung fuel tank is a fuel tank that has a portion of the tank below the bumper tube or chassis rails and therefore is to have a fuel tank protector bar fitted.
5. Allowed track measurements for VT, VX, VY, VZ, Commodore and Monaro Front 1645 mm Rear 1665 mm
6. Any front mud protection guards under cars to protect engine or suspension components from mud and dirt must not be any lower than 150 mm from ground and must not attach to bumper cover.
7. Page 41 Table 4: To include alloy tech engine VZ and VE Commodore. Bore 94 mm, Stroke 85.6 mm, Capacity 3.6 Litre
8. Wheelbase measurements for XD/XE Falcon should be 2818mm.

CLARIFICATIONS FOR STREET STOCKS

1. Clarification on stub axles VS Commodore onwards: The bearing carrier and hub as a unit is classed as stub axle assembly.
2. Standard replacement A.R.P. conrod bolts are acceptable.
3. Late model EL Falcon, either of the top two differential mounting positions may be used.
4. Misprint in specification book: XD/XE Falcon wheel base should be 2818 mm
5. BA Falcon dimensions: Wheel base 2829mm, Front track 1568 mm, Rear track 1586 mm (includes 15mm)
6. Allowable valve sized Ecotech Series II Engine: Exhaust 38.74 mm, Inlet 45.85 mm
7. Page 30 – 24D Book Deletion: Internally adjustable shock absorbers permitted if they are adjusted by removing from car to adjust by compressing etc.
8. Wheelbase measurements for XD/XE Falcon should be 2818mm.

Technical Members contact details:-

Des Alfirevich – Technical Director - 0419 929 315
 Tony O'Neill – SSA of NSW, NSW - 0401 719 402
 Peter Harris – NTSCI, Northern Territory - 0418 838 558
 Harold Burgess – TSCF, Tasmania - 0429 014 447

Bill Peall – QSCA, Queensland - 0407 791 449
 Neville Pike – VSCF, Victoria - 0427 401 030
 Dave Helyar – NASR SA – South Australia - 0418 828 881
 Peter Theyer – WASCF, Western Australia – (08) 9841 4999